

WC Series Water Treatment Systems



WC Series

High-Volume Water Cannons

Typical applications include:

- Rental Yards
- Lumber Yards
- Mining Operations
- Heavy Equipment Dealers
- Solid Waste Haulers

Standard with Unit:

Single remote





The High-Volume Water Cannon System acts like a water blaster, pre-washing heavy equipment and tracked vehicles. The tough, high gallon-per-minute centrifugal system blasts away mud and dirt for an easier and shorter workload during the pressure wash cycle.

MODEL NUMBER	DESCRIPTION	GPM @ PSI	HORSEPOWER	DIMENSIONS (LxWxH)	SHIP WT.
WC-100-0ME3	Mud blasting pump system with centrifugal separator (Specify 208-230V, 3Ø, 20-22.0A or 460V, 3Ø, 10.0A)	100 @ 60	7.5	42x20x66in.	500 lb.
WC-150-0ME3	Mud blasting pump system with centrifugal separator (Specify 208-230V, 3Ø, 38.0A or 460V, 3Ø, 19.0A)	150 @ 80	15.0	45x21x67in.	650 lb.
WC-400T-0ME3	Truck wheel wash pump system, for minimum vertical lift feed, 5 or 6-ft. or tank feed (Specify 230V, 3Ø, 116.0A, 60Hz motor or 460V, 3Ø, 58.0A)	400 @ 125	50.0	58x28x75in.	1178 lb.
Accessories:					
PART NUMBER	DESCRIPTION	FITS MODELS			
12-0084	Surge suppressor - Eliminates water logging and failures	WC-100 & W	/C-150		
15-2001	Hose for water cannon - 100-ft. x 1½-in. ID with couplings	WC-100 & W	/C-150		
18-2009	Adjustable fire hose nozzle - Adjustable spray settings, 150 GPM	WC-100 & W	/C-150		
22-0322	Metal foot-valve - 2-in.	WC-100-0M	E3		
22-0323	Metal foot-valve - 3-in.	WC-150-0M	E3		
22-0400	Metal foot-valve - 4-in.	All models			
50-2001	Hose reel for 1½-in. booster hose - 100-ft.	WC-100 & W	/C-150		
RC-0015-0001	Remote switch assembly - Comes standard with one remote	WC-100 & W	/C-150		
Options:					
PART NUMBER	DESCRIPTION	FITS MODELS			
WX-0002	460V, 3Ø, 10.0A - Upgrades 208-230V model to operate at 460V	WC-100-0ME	E3		
WX-0003	460V, 3Ø, 19.0A - Upgrades 208-230V model to operate at 460V	WC-150-0M	E3		
WA-0003	400V, 39, 13.0A - upgrades 200-230V illouer to operate at 400V	WG-130-OWI	LJ		

CHV Series

Cold Water Electric Belt Drive Pressure Washers



Receive more power with less pressure. This cold water, high-volume pressure washer is the perfect answer for applications that require cleaning of heavy solids, especially from large industrial equipment.

Ideal for wash bay set-ups.

Pump:

Belt drive diaphragm pump with pulsation dampener

Motor:

Totally enclosed fan-cooled electric motor with thermal overload protection | 10-foot power cord

Components:

Pressure regulator with manual dump lever and gauge | Makeup water shut-off solenoid and flow switch on outlet | Time delay shutdown

Unit Includes:

Typical Water Treatment Installation:

CHV-0525-0ME3 is connected to optional 300-gallon tank, CX-0072, which is connected to optional sump pump and in-ground fiberglass pit from the water treatment line.



MODEL NUMBER	DESCRIPTION	GPM @ PSI	HORSEPOWER/MOTOR	DIMENSIONS (LxWxH)	SHIP WT.
CHV-0525-0ME1	Cold water stationary electric belt-driven pressure washer	25 @ 500	10.0 HP, 230V, 1Ø, 41.5A	38x23.5x24in.	432 lb.
CHV-0525-0ME3	Cold water stationary electric belt-driven pressure washer	25 @ 500	10.0 HP, 230V, 3Ø, 25.6A	38x23.5x24in.	407 lb.

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
16-0440	Replacement gun - Replacement high-volume long range gun with adjustable pattern from straight stream to cone mist	All models
50-0185	Hose reel - For convenient storage of hose; holds up to 200-ft. of ¾-in. hose	All models
Options:		

PART NUMBER	DESCRIPTION	FITS MODELS
CX-0072	300-gallon tank - 300-gallon tank with stand, suction hose and float	All models
CX-0073	460V, 3Ø models - For when you have 460V of power available	All models
CX-0074	18-in. stand - Raises unit off of ground	All models
CX-0075	Remote start control box - For when unit is not near spraying location	All models

CHV Series Application

Ideal for heavy mud removal applications.
The high volume GPM cuts cleaning time significantly.





5500 Commerce Blvd. Suite A Rohnert Park, CA 94928 (707) 793-4800 www.WaterForReuse.com info@usHydroTech.com

